



T I E F F E
CHEMICAL SOLVING

ACQUABRITE ECO HW PLUS

CHLORINATED ALCALINE DISHWASHER DETERGENT FOR VERY HARD WATERS

It is a liquid chlorinated detergent for mechanic washing in tunnel dishwashers or basket dishwashers when there is a conspicuous residual of amid or for particularly dirty residus.

It is a caustic-based product containing water softeners, padding agents and free chlorine that has an effective sanitizing action during the washing cycle. It is studied to be effective in presence of very hard waters.

It can safely be used on pots, cutlery, etc. It cannot be safely used on aluminum.

DIRECTIONS FOR USE

It is used with a 2 - 5 ml concentration per each liter of water based on the real quantity of dirt and/or considering how fast the tunnel washing chain is, etc.

We advise to dose the detergent with automatic dosing pump, allowing an accurate control and dosage during the washing cycle.

The following conditions are advised:

- Concentration: 2 - 5 ml per liter
- Temperature: 50 to 55 degrees Celsius
- Washing cycle length: 60 seconds minimum

During the washing and the rinsing cycle, the entire surface of pots, dishes and cutlery must be reached by the solution; periodically check that the nozzles are not obstructed and periodically (ex: monthly) descale the dishwasher with REMO KAL

DOSING DIRECTIONS

Water Hardness

Based on water hardness in °F (French degrees)

soft 0 -15	2 g/l
medium 15 - 25	3 g/l
hard 25 - 40	5 g/l

PRECAUTIONS

Refer to the safety data sheets

Revision: MC 03/16